

LOAD & INFLATION

TABLE B

METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

ENGLISH UNITS OF MEASURE

TIRE TYPE NOMENCLATURE			
TRA	TIRE TYPE	MAX. SPEED	
		SPEED INDEX	SPEED INDEX
		A8/B	D
R-1	Drive Wheel, Regular Tread	30 MPH	40 MPH
R-1W	Drive Wheel, Wet Traction Tread	30 MPH	40 MPH
R-2	Cane & Rice, Drive Wheel, Deep Tread	25 MPH	—

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
230/95R48	LI						114		121		123	126	129	132	134		
	SINGLES lbs		1430	1710	2040	2270	2600	2910	3200	3300	3420	3740	4080	4400	4680		
	DUALS lbs		1260	1500	1800	2000	2290	2560	2820	2900	3010	3290	3590	3870	4120		
	TRIPLES lbs		1170	1400	1670	1860	2130	2390	2620	2710	2800	3070	3350	3610	3840		
280/70R16	LI						95		102		108	112					
	SINGLES lbs		855	1020	1200	1360	1520	1710	1870	2040	2200	2470					
	DUALS lbs		750	900	1060	1200	1340	1500	1650	1800	1940	2170					
	TRIPLES lbs		700	840	980	1120	1250	1400	1530	1670	1800	2030					
280/70R18	LI						97		104		110	114					
	SINGLES lbs		910	1070	1280	1430	1610	1820	1980	2150	2340	2600					
	DUALS lbs		800	940	1130	1260	1420	1600	1740	1890	2060	2290					
	TRIPLES lbs		750	880	1050	1170	1320	1490	1620	1760	1920	2130					
280/70R20	LI						99		106		112	116					
	SINGLES lbs		935	1140	1320	1520	1710	1870	2090	2270	2470	2760					
	DUALS lbs		820	1000	1160	1340	1500	1650	1840	2000	2170	2430					
	TRIPLES lbs		770	930	1080	1250	1400	1530	1710	1860	2030	2260					
280/85R24	LI						108		115								
	SINGLES lbs		1230	1480	1710	1930	2200	2470	2680								
	DUALS lbs		1080	1300	1500	1700	1940	2170	2360								
	TRIPLES lbs		1010	1210	1400	1580	1800	2030	2200								
290/95R34	LI						119		125		129	131					
	SINGLES lbs		1650	2040	2340	2680	3000	3300	3640	3860	4080	4300					
	DUALS lbs		1450	1800	2060	2360	2640	2900	3200	3400	3590	3780					
	TRIPLES lbs		1350	1670	1920	2200	2460	2710	2980	3170	3350	3530					
300/70R20	LI						102		110		116	120					
	SINGLES lbs		1050	1280	1480	1650	1870	2090	2340	2540	2760	3080					
	DUALS lbs		920	1130	1300	1450	1650	1840	2060	2240	2430	2710					
	TRIPLES lbs		860	1050	1210	1350	1530	1710	1920	2080	2260	2530					
320/85R24	LI						115		122								
	SINGLES lbs		1480	1820	2090	2400	2680	3000	3300								
	DUALS lbs		1300	1600	1840	2110	2360	2640	2900								
	TRIPLES lbs		1210	1490	1710	1970	2200	2460	2710								
320/85R28	LI						118		124								
	SINGLES lbs		1610	1930	2270	2600	2910	3200	3520								
	DUALS lbs		1420	1700	2000	2290	2560	2820	3100								
	TRIPLES lbs		1320	1580	1860	2130	2390	2620	2890								

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
320/85R34	LI						121		127		131	133					
	SINGLES lbs		1760	2150	2470	2830	3200	3520	3860	4080	4300	4540					
	DUALS lbs		1550	1890	2170	2490	2820	3100	3400	3590	3780	4000					
	TRIPLES lbs		1440	1760	2030	2320	2620	2890	3170	3350	3530	3720					
320/85R38	LI						123		129		133	135	138	141	143		
	SINGLES lbs		1870	2270	2600	3000	3420	3740	4080	4300	4540	4800	5200	5680	6000		
	DUALS lbs		1650	2000	2290	2640	3010	3290	3590	3780	4000	4220	4580	5000	5280		
	TRIPLES lbs		1530	1860	2130	2460	2800	3070	3350	3530	3720	3940	4260	4660	4920		
320/90R42	LI						126		133		136	139					
	SINGLES lbs		2090	2470	2910	3300	3740	4180	4540	4800	4940	5360					
	DUALS lbs		1840	2170	2560	2900	3290	3680	4000	4220	4350	4720					
	TRIPLES lbs		1710	2030	2390	2710	3070	3430	3720	3940	4050	4400					
320/90R46	LI						127		135		138	140	144	146	148		
	SINGLES lbs		2150	2600	3000	3420	3860	4300	4800	5080	5200	5520	6150	6600	6950		
	DUALS lbs		1890	2290	2640	3010	3400	3780	4220	4470	4580	4860	5410	5810	6120		
	TRIPLES lbs		1760	2130	2460	2800	3170	3530	3940	4170	4260	4530	5040	5410	5700		
320/90R50	LI						129		136		140	142	145	148			
	SINGLES lbs		2270	2760	3200	3640	4080	4540	4940	5200	5520	5840	6400	6950			
	DUALS lbs		2000	2430	2820	3200	3590	4000	4350	4580	4860	5140	5630	6120			
	TRIPLES lbs		1860	2260	2620	2980	3350	3720	4050	4260	4530	4790	5250	5700			
320/90R54	LI						131		138		141	143	146	149			
	SINGLES lbs		2340	2830	3300	3740	4300	4680	5200	5520	5680	6000	6600	7150			
	DUALS lbs		2060	2490	2900	3290	3780	4120	4580	4860	5000	5280	5810	6290			
	TRIPLES lbs		1920	2320	2710	3070	3530	3840	4260	4530	4660	4920	5410	5860			
340/85R24	LI						119		125								
	SINGLES lbs		1650	1980	2270	2600	3000	3300	3640								
	DUALS lbs		1450	1740	2000	2290	2640	2900	3200								
	TRIPLES lbs		1350	1620	1860	2130	2460	2710	2980								
340/85R28	LI						121		127								
	SINGLES lbs		1760	2090	2470	2830	3200	3520	3860								
	DUALS lbs		1550	1840	2170	2490	2820	3100	3400								
	TRIPLES lbs		1440	1710	2030	2320	2620	2890	3170								
360/70R20	LI						113		120		125	129					
	SINGLES lbs		1390	1650	1930	2200	2540	2760	3080	3300	3640	4080					
	DUALS lbs		1220	1450	1700	1940	2240	2430	2710	2900	3200	3590					
	TRIPLES lbs		1140	1350	1580	1800	2080	2260	2530	2710	2980	3350					

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
360/70R28	LI						118		125								
	SINGLES lbs		1610	1930	2270	2600	2910	3300	3640								
	DUALS lbs		1420	1700	2000	2290	2560	2900	3200								
	TRIPLES lbs		1320	1580	1860	2130	2390	2710	2990								
380/70R24	LI						119		125								
	SINGLES lbs		1650	1980	2270	2600	3000	3300	3640								
	DUALS lbs		1450	1740	2000	2290	2640	2900	3200								
	TRIPLES lbs		1350	1620	1860	2130	2460	2710	2980								
380/70R28	LI						121		127								
	SINGLES lbs		1760	2090	2470	2830	3200	3520	3860								
	DUALS lbs		1550	1840	2170	2490	2820	3100	3400								
	TRIPLES lbs		1440	1710	2030	2320	2620	2890	3170								
380/80R38	LI						130		137		140	142					
	SINGLES lbs		2270	2760	3200	3640	4180	4540	5080	5360	5520	5840					
	DUALS lbs		2000	2430	2820	3200	3680	4000	4470	4720	4860	5140					
	TRIPLES lbs		1860	2260	2620	2980	3430	3720	4170	4400	4530	4790					
380/85R24	LI						124		131								
	SINGLES lbs		1930	2340	2760	3080	3520	3860	4300								
	DUALS lbs		1700	2060	2430	2710	3100	3400	3780								
	TRIPLES lbs		1580	1920	2260	2530	2890	3170	3530								
380/85R28	LI						126		133								
	SINGLES lbs		2090	2540	2910	3300	3740	4180	4540								
	DUALS lbs		1840	2240	2560	2900	3290	3680	4000								
	TRIPLES lbs		1710	2080	2390	2710	3070	3430	3720								
380/85R30	LI						127		135								
	SINGLES lbs		2150	2600	3000	3420	3860	4300	4800								
	DUALS lbs		1890	2290	2640	3010	3400	3780	4220								
	TRIPLES lbs		1760	2130	2460	2800	3170	3530	3940								
380/85R34	LI						129		137		140	142	145				
	SINGLES lbs		2270	2760	3200	3640	4080	4540	5080	5360	5520	5840	6400				
	DUALS lbs		2000	2430	2820	3200	3590	4000	4470	4720	5860	5140	5630				
	TRIPLES lbs		1860	2260	2620	2980	3350	3720	4170	4400	4530	4790	5250				
385/85R34	LI						130		138		141	143	146				
	SINGLES lbs		2340	2830	3300	3740	4180	4680	5200	5360	5680	6000	6600				
	DUALS lbs		2060	2490	2900	3290	3680	4120	4580	4720	5000	5280	5810				
	TRIPLES lbs		1920	2320	2710	3070	3430	3840	4260	4400	4660	4920	5410				
380/90R46	LI						137		144		147	149	152				
	SINGLES lbs		2830	3300	3860	4400	5080	5520	6150	6400	6800	7150	7850				
	DUALS lbs		2490	2900	3400	3870	4470	4860	5410	5630	5980	6290	6910				
	TRIPLES lbs		2320	2710	3170	3610	4170	4530	5040	5250	5580	5860	6440				

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
380/90R50	LI						138		145		148	151					
	SINGLES lbs		2910	3520	4080	4680	5200	5840	6400	6800	6950	7600					
	DUALS lbs		2560	3100	3590	4120	4580	5140	5630	5980	6120	6690					
	TRIPLES lbs		2390	2890	3350	3840	4260	4790	5250	5580	5700	6230					
380/90R54	LI						140		146		150	152					
	SINGLES lbs		3000	3640	4300	4800	5520	6000	6600	6950	7400	7850					
	DUALS lbs		2640	3200	3780	4220	4860	5280	5810	6120	6510	6910					
	TRIPLES lbs		2460	2980	3530	3940	4530	4920	5410	5700	6070	6440					
380/105R50	LI						143		150		153	155	158	161	163	165	168
	SINGLES lbs		3300	3960	4680	5360	6000	6600	7400	7600	8050	8550	9350	10200	10700	11400	12300
	DUALS lbs		2900	3480	4120	4720	5280	5810	6510	6690	7080	7520	8230	8980	9420	10030	10825
	TRIPLES lbs		2710	3250	3840	4400	4920	5410	6070	6230	6600	7010	7670	8360	8770	9350	10085
385/85R34	LI						129		137		140	142	145				
	SINGLES lbs		2270	2760	3200	3640	4080	4540	5080	5360	5520	5840	6400				
	DUALS lbs		2000	2430	1820	3200	3590	4000	4470	4720	4860	5140	5630				
	TRIPLES lbs		1860	2260	2620	2980	3350	3720	4170	4400	4530	4790	5250				
420/70R24	LI						123		130								
	SINGLES lbs		1930	2270	2680	3080	3420	3860	4180								
	DUALS lbs		1700	2000	2360	2710	3010	3400	3680								
	TRIPLES lbs		1580	1860	2200	2530	2800	3170	3430								
420/80R46	LI						139		145		149	151	154	156	159	161	
	SINGLES lbs		2910	3520	4080	4680	5360	5840	6400	6800	7150	7600	8250	8800	9650	10200	
	DUALS lbs		2560	3100	3590	4120	4720	5140	5630	5980	6290	6690	7260	7740	8490	8980	
	TRIPLES lbs		2390	2890	3350	3840	4400	4790	5250	5580	5860	6230	6770	7220	7910	8360	
420/85R24	LI						129		137								
	SINGLES lbs		2270	2760	3200	3640	4080	4540	5080								
	DUALS lbs		2000	2430	2820	3200	3590	4000	4470								
	TRIPLES lbs		1860	2260	2620	2980	3350	3720	4170								
420/85R26	LI						131		138								
	SINGLES lbs		2340	2830	3300	3740	4300	4680	5200								
	DUALS lbs		2060	2490	2900	3290	3780	4120	4580								
	TRIPLES lbs		1920	2320	2710	3070	3530	3840	4260								
420/85R28	LI						132		139								
	SINGLES lbs		2470	2910	3420	3860	4400	4940	5360								
	DUALS lbs		2170	2560	3010	3400	3870	4350	4720								
	TRIPLES lbs		2030	2390	2800	3170	3610	4050	4400								
420/85R30	LI						133		140								
	SINGLES lbs		2540	3000	3520	4080	4540	5080	5520								
	DUALS lbs		2240	2640	3100	3590	4000	4470	4860								
	TRIPLES lbs		2080	2460	2890	3350	3720	4170	4530								

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
420/85R34	LI					135		142		145	147						
	SINGLES lbs	2680	3200	3740	4300	4800	5360	5840	6150	6400	6800						
	DUALS lbs	2360	2820	3290	3780	4220	4720	5140	5410	5630	5980						
	TRIPLES lbs	2200	2620	3070	3530	3940	4400	4790	5040	5250	5580						
420/85R38	LI					137		144									
	SINGLES lbs	2830	3420	3960	4540	5080	5680	6150									
	DUALS lbs	2490	3010	3480	4000	4470	5000	5410									
	TRIPLES lbs	2320	2800	3250	3720	4170	4660	5040									
420/90R30	LI					135		142		145							
	SINGLES lbs	2680	3200	3740	4180	4800	5360	5840	6150	6400							
	DUALS lbs	2360	2820	3290	3680	4220	4720	5140	5410	5630							
	TRIPLES lbs	2200	2620	3070	3430	3940	4400	4790	5040	5250							
460/85R30	LI					138		145									
	SINGLES lbs	2910	3520	4080	4680	5200	5840	6400									
	DUALS lbs	2560	3100	3590	4120	4580	5140	5630									
	TRIPLES lbs	2390	2890	3350	3840	4260	4790	5250									
460/85R34	LI					140	144	147									
	SINGLES lbs	3080	3640	4300	4940	5520	6150	6800									
	DUALS lbs	2710	3200	3780	4350	4860	5410	5980									
	TRIPLES lbs	2530	2980	3530	4050	4530	5040	5580									
460/85R38	LI					142		149									
	SINGLES lbs	3200	3860	4540	5200	5840	6400	7150									
	DUALS lbs	2820	3400	4000	4580	5140	5630	6290									
	TRIPLES lbs	2620	3170	3720	4260	4790	5250	5860									
460/85R42	LI					144		150									
	SINGLES lbs	3420	4080	4800	5360	6150	6800	7400									
	DUALS lbs	3010	3590	4220	4720	5410	5980	6510									
	TRIPLES lbs	2800	3350	3940	4400	5040	5580	6070									
480/65R24	LI					127		133		137	140						
	SINGLES lbs	2150	2600	3000	3420	3860	4180	4540	4800	5080	5520						
	DUALS lbs	1890	2290	2640	3010	3400	3680	4000	4220	4470	4860						
	TRIPLES lbs	1760	2130	2460	2800	3170	3430	3720	3940	4170	4530						
480/70R24	LI					131		138									
	SINGLES lbs	2340	2830	3300	3740	4300	4680	5200									
	DUALS lbs	2060	2490	2900	3290	3780	4120	4580									
	TRIPLES lbs	1920	2320	2710	3070	3530	3840	4260									
480/70R28	LI					133		140									
	SINGLES lbs	2540	3000	3520	4080	4540	5080	5520									
	DUALS lbs	2240	2640	3100	3590	4000	4470	4860									
	TRIPLES lbs	2080	2460	2890	3350	3720	4170	4530									

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES														
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58
480/70R30	LI					134		141		145	147	150	152			
	SINGLES lbs	2600	3080	3640	4180	4680	5200	5680	6000	6400	6800	7400	7850			
	DUALS lbs	2290	2710	3200	3680	4120	4580	5000	5280	5630	5980	6510	6910			
	TRIPLES lbs	2130	2530	2980	3430	3840	4260	4660	4920	5250	5580	6070	6440			
480/70R34	LI					136		143		146	149	152	155			
	SINGLES lbs	2760	3300	3860	4400	4940	5520	6000	6400	6600	7150	7850	8550			
	DUALS lbs	2430	2900	3400	3870	4350	4860	5280	5630	5810	6290	6910	7520			
	TRIPLES lbs	2260	2710	3170	3610	4050	4530	4920	5250	5410	5860	6440	7010			
480/70R38	LI					138		145								
	SINGLES lbs	2910	3520	4080	4680	5200	5840	6400								
	DUALS lbs	2560	3100	3590	4120	4580	5140	5630								
	TRIPLES lbs	2390	2890	3350	3840	4260	4790	5250								
480/80R30	LI					139		145		149	151	154	156	159		
	SINGLES lbs	2910	3520	4080	4680	5360	5840	6400	6800	7150	7600	8250	8800	9650		
	DUALS lbs	2560	3100	3590	4120	4720	5140	5630	5980	6290	6690	7260	7740	8490		
	TRIPLES lbs	2390	2890	3350	3840	4400	4790	5250	5580	5860	6230	6770	7220	7910		
480/80R38	LI					142		149								
	SINGLES lbs	3300	3960	4540	5200	5840	6600	7150								
	DUALS lbs	2900	3480	4000	4580	5140	5810	6290								
	TRIPLES lbs	2710	3250	3720	4260	4790	5410	5860								
480/80R42	LI					144		151		154						
	SINGLES lbs	3420	4080	4800	5520	6150	6950	7600	8050	8250						
	DUALS lbs	3010	3590	4220	4860	5410	6120	6690	7080	7260						
	TRIPLES lbs	2800	3350	3940	4530	5040	5700	6230	6600	6770						
480/80R46	LI					145		152		155	158					
	SINGLES lbs	3640	4300	5080	5680	6400	7150	7850	8250	8550	9350					
	DUALS lbs	3200	3780	4470	5000	5630	6290	6910	7260	7520	8230					
	TRIPLES lbs	2980	3530	4170	4660	5250	5860	6440	6770	7010	7670					
480/80R50	LI					147		154		157	159					
	SINGLES lbs	3740	4540	5200	6000	6800	7600	8250	8550	9100	9650					
	DUALS lbs	3290	4000	4580	5280	5980	6690	7260	7520	8010	8490					
	TRIPLES lbs	3070	3720	4260	4920	5580	6230	6770	7010	7460	7910					
480/85R34	LI					142		149								
	SINGLES lbs	3300	3960	4540	5200	5840	6600	7150								
	DUALS lbs	2900	3480	4000	4580	5140	5810	6290								
	TRIPLES lbs	2710	3250	3720	4260	4790	5410	5860								
520/70R38	LI					143		150								
	SINGLES lbs	3300	3960	4680	5200	6000	6600	7400								
	DUALS lbs	2900	3480	4120	4580	5280	5810	6510								
	TRIPLES lbs	2710	3250	3840	4260	4920	5410	6070								

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
520/85R34	LI						146		154		157	159	162				
	SINGLES lbs		3740	4400	5200	6000	6600	7400	8250	8550	9100	9650	10500				
	DUALS lbs		3290	3870	4580	5280	5810	6510	7260	7520	8010	8490	9240				
	TRIPLES lbs		3070	3610	4260	4920	5410	6070	6770	7010	7460	7910	8610				
520/85R38	LI						148		155								
	SINGLES lbs		3860	4680	5520	6150	6950	7850	8550								
	DUALS lbs		3400	4120	4860	5410	6120	6910	7520								
	TRIPLES lbs		3170	3840	4530	5040	5700	6440	7010								
520/85R42	LI						150		157		160	162	165				
	SINGLES lbs		4080	4940	5680	6600	7400	8250	9100	9350	9900	10500	11400				
	DUALS lbs		3590	4350	5000	5810	6510	7260	8010	8230	8710	9240	10030				
	TRIPLES lbs		3350	4050	4660	5410	6070	6770	7460	7670	8120	8610	9350				
520/85R46	LI						151		158								
	SINGLES lbs		4300	5080	6000	6800	7600	8550	9350								
	DUALS lbs		3780	4470	5280	5980	6690	7520	8230								
	TRIPLES lbs		3530	4170	4920	5580	6230	7010	7670								
540/65R24	LI						134		140								
	SINGLES lbs		2600	3080	3640	4080	4680	5080	5520								
	DUALS lbs		2290	2710	3200	3590	4120	4470	4860								
	TRIPLES lbs		2130	2530	2980	3350	3840	4170	4530								
540/65R30	LI						137		143		147	150					
	SINGLES lbs		2830	3420	3960	4540	5080	5680	6000	6400	6800	7400					
	DUALS lbs		2490	3010	3480	4000	4470	5000	5280	5630	5980	6510					
	TRIPLES lbs		2320	2800	3250	3720	4170	4660	4920	5250	5580	6070					
540/65R34	LI						140		145		149	152					
	SINGLES lbs		3000	3640	4180	4800	5520	6000	6400	6800	7150	7850					
	DUALS lbs		2640	3200	3680	4220	4860	5280	5630	5980	6290	6910					
	TRIPLES lbs		2460	2980	3430	3940	4530	4920	5250	5580	5860	6440					
540/65R38	LI						141		147								
	SINGLES lbs		3200	3860	4400	5080	5680	6150	6800								
	DUALS lbs		2820	3400	3870	4470	5000	5410	5980								
	TRIPLES lbs		2620	3170	3610	4170	4660	5040	5580								
580/85R42	LI						156		163		166	168					
	SINGLES lbs		4800	5840	6800	7850	8800	9650	10700	11000	11700	12300					
	DUALS lbs		4220	5140	5980	6910	7740	8490	9420	9680	10300	10820					
	TRIPLES lbs		3940	4790	5580	6440	7220	7910	8770	9020	9590	10080					
600/65R28	LI						142		147		152	154					
	SINGLES lbs		3300	3860	4540	5200	5840	6400	6800	7400	7850	8250					
	DUALS lbs		2900	3400	4000	4580	5140	5630	5980	6510	6910	7260					
	TRIPLES lbs		2710	3170	3720	4260	4790	5250	5580	6070	6440	6770					

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
600/65R38	LI						147		153		156	159	162	165			
	SINGLES lbs		3740	4540	5200	6000	6800	7400	8050	8550	8800	9650	10500	11400			
	DUALS lbs		3290	4000	4580	5280	5980	6510	7080	7520	7740	8490	9240	10030			
	TRIPLES lbs		3070	3720	4260	4920	5580	6070	6600	7010	7220	7910	8610	9350			
600/70R28	LI						145		152		155	157	161	164			
	SINGLES lbs		3640	4300	5080	5680	6400	7150	7850	8250	8550	9100	10200	11000			
	DUALS lbs		3200	3780	4470	5000	5630	6290	6910	7260	7520	8000	8980	9680			
	TRIPLES lbs		2980	3530	4170	4660	5250	5860	6440	6770	7010	7460	8360	9020			
600/70R30	LI						146		152		156	158	162				
	SINGLES lbs		3640	4400	5200	5840	6600	7400	7850	8550	8800	9350	10500				
	DUALS lbs		3200	3870	4580	5140	5810	6510	6910	7520	7740	8230	9240				
	TRIPLES lbs		2980	3610	4260	4790	5410	6070	6440	7010	7220	7670	8610				
620/70R42	LI						153		160		164	166					
	SINGLES lbs		4540	5360	6400	7150	8050	9100	9900	10500	11000	11700					
	DUALS lbs		4000	4720	5630	6290	7080	8010	8710	9240	9680	10300					
	TRIPLES lbs		3720	4400	5250	5860	6600	7460	8120	8610	9020	9590					
650/65R38	LI						151		157		160	163	166				
	SINGLES lbs		4180	5080	5840	6800	7600	8250	9100	9650	9900	10700	11700				
	DUALS lbs		3680	4470	5140	5980	6690	7260	8000	8500	8712	9416	10296				
	TRIPLES lbs		3430	4170	4790	5580	6230	6770	7460	7910	8120	8770	9600				
650/75R32	LI						154		161		164	166	169	172			
	SINGLES lbs		4540	5520	6400	7400	8250	9100	10200	10700	11000	11700	12800	13900			
	DUALS lbs		4000	4860	5630	6510	7260	8010	8980	9420	9680	10300	11260	12230			
	TRIPLES lbs		3720	4530	5250	6070	6770	7460	8360	8770	9020	9590	10500	11400			
650/85R38	LI						160		167		170	173					
	SINGLES lbs		5520	6600	7850	8800	9900	11000	12000	12800	13200	14300					
	DUALS lbs		4860	5810	6910	7740	8710	9680	10560	11260	11620	12580					
	TRIPLES lbs		4530	5410	6440	7220	8120	9020	9840	10500	10820	11730					
710/70R38	LI						159		166		169	171					
	SINGLES lbs		5360	6400	7400	8550	9650	10700	11700	12300	12800	13600					
	DUALS lbs		4720	5630	6510	7520	8490	9420	10300	10820	11260	11970					
	TRIPLES lbs		4400	5250	6070	7010	7910	8770	9590	10090	10500	11150					
710/70R42	LI						160		168		171	173					
	SINGLES lbs		5520	6600	7850	8800	9900	11000	12300	12800	13600	14300					
	DUALS lbs		4860	5810	6910	7740	8710	9680	10820	11260	11970	12580					
	TRIPLES lbs		4530	5410	6440	7220	8120	9020	10090	10500	11150	11730					

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

ENGLISH UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		psi	6	9	12	15	17	20	23	26	29	35	41	46	52	58	64
750/65R26	LI						153		159		163	166	169				
	SINGLES lbs		4540	5360	6400	7150	8050	8800	9650	10200	10700	11700	12800				
	DUALS lbs		4000	4720	5630	6290	7080	7740	8490	8980	9420	10300	11260				
	TRIPLES lbs		3720	4400	5250	5860	6600	7220	7910	8360	8770	9590	10500				
800/65R32	LI						159		166		169	172					
	SINGLES lbs		5360	6600	7600	8800	9650	10700	11700	12300	12800	13900					
	DUALS lbs		4720	5810	6690	7740	8490	9420	10300	10820	11260	12230					
	TRIPLES lbs		4400	5410	6230	7220	7910	8770	9590	10090	10500	11400					
800/70R38	LI						166		173		176	178	181				
	SINGLES lbs		6400	7600	9100	10200	11700	12800	14300	14800	15700	16500	18200				
	DUALS lbs		5630	6690	8010	8980	10300	11260	12580	13020	13820	14520	16020				
	TRIPLES lbs		5250	6230	7460	8360	9590	10500	11730	12140	12870	13530	14920				
900/50R42	LI						161		168								
	SINGLES lbs		5680	6800	7850	9100	10200	11400	12300								
	DUALS lbs		5000	5980	6910	8010	8980	10030	10820								
	TRIPLES lbs		4660	5580	6440	7460	8360	9350	10090								
900/60R32	LI						163		169		173	176					
	SINGLES lbs		5840	7150	8250	9350	10700	11700	12800	13900	14300	15700					
	DUALS lbs		5140	6290	7260	8230	9420	10300	11260	12230	12580	13820					
	TRIPLES lbs		4790	5860	6770	7670	8770	9590	10500	11400	11730	12870					
900/75R32	LI						172		179		182	184					
	SINGLES lbs		7850	9350	10700	12300	13900	15700	17100	17600	18700	19800					
	DUALS lbs		6910	8230	9420	10820	12230	13820	15050	15490	16460	17420					
	TRIPLES lbs		6440	7670	8770	10090	11400	12870	14020	14430	15330	16240					

NOTES:

1. For shipping purposes, tire inflation pressures may be increased to 30 psi (210 kPa). Inflation pressure must be adjusted to correct operating inflation before placing tires in service.
2. For transport service above 20 mph (30 km/h), recommended minimum inflation pressure is 8 psi (60 kPa).
3. For tires used in cyclic loading service see Table F1.
4. For transport service and operations which do not require sustained high torque, the following limits at various speeds apply with no change in inflation pressure.

MAX. SPEED	% CHANGE IN TABLE
10 mph (15 km/h)	+34% (except hillside combines)
15 mph (25 km/h)	+11% (except hillside combines)
20 mph (30 km/h)	+7%
25 mph (40 km/h)	None
30 mph (50 km/h)	None

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC RADIAL PLY AGRICULTURAL TRACTOR DRIVE WHEEL TIRES

BASIC TIRE LOAD RATINGS FOR TIRE SELECTION

METRIC UNITS OF MEASURE

TIRE TYPE NOMENCLATURE			
		MAX. SPEED	
		SPEED INDEX	SPEED INDEX
TRA	TIRE TYPE	A8/B	D
R-1	Drive Wheel, Regular Tread	50 KM/H	65 KM/H
R-1W	Drive Wheel, Wet Traction Tread	50 KM/H	65 KM/H
R-2	Cane & Rice, Drive Wheel, Deep Tread	40 KM/H	—

TIRE SIZE		INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
			kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
			bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
230/95R48		LI						114		121		123	126	129	132	134		
	SINGLES kg		650	775	925	1030	1180	1320	1450	1500	1550	1700	1850	2000	2120			
	DUALS kg		570	680	810	910	1040	1160	1280	1320	1360	1500	1630	1760	1870			
	TRIPLES kg		530	640	760	840	970	1080	1190	1230	1270	1390	1520	1640	1740			
280/70R16		LI					95		102		108	112						
	SINGLES kg		387	462	545	615	690	775	850	925	1000	1120						
	DUALS kg		340	410	480	540	610	680	750	810	880	990						
	TRIPLES kg		320	380	450	500	570	640	700	760	820	920						
280/70R18		LI					97		104		110	114						
	SINGLES kg		412	487	580	650	730	825	900	975	1060	1180						
	DUALS kg		360	430	510	570	640	730	790	860	930	1040						
	TRIPLES kg		340	400	480	530	600	680	740	800	870	970						
280/70R20		LI					99		106		112	116						
	SINGLES kg		425	515	600	690	775	850	950	1030	1120	1250						
	DUALS kg		370	450	530	610	680	750	840	910	990	1100						
	TRIPLES kg		350	420	490	570	640	700	780	840	920	1030						
280/85R24		LI					108		115									
	SINGLES kg		560	670	775	875	1000	1120	1215									
	DUALS kg		490	590	680	770	880	990	1070									
	TRIPLES kg		460	550	640	720	820	920	1000									
290/95R34		LI					119		125		129	131						
	SINGLES kg		750	925	1060	1215	1360	1500	1650	1750	1850	1950						
	DUALS kg		660	810	930	1070	1200	1320	1450	1540	1630	1720						
	TRIPLES kg		620	760	870	1000	1120	1230	1350	1440	1520	1600						
300/70R20		LI					102		110		116	120						
	SINGLES kg		475	580	670	750	850	950	1060	1150	1250	1400						
	DUALS kg		420	510	590	660	750	840	930	1010	1100	1230						
	TRIPLES kg		390	480	550	620	700	780	870	940	1030	1150						
320/85R24		LI					115		122									
	SINGLES kg		670	825	950	1090	1215	1360	1500									
	DUALS kg		590	730	840	960	1070	1200	1320									
	TRIPLES kg		550	680	780	890	1000	1120	1230									
320/85R28		LI					118		124									
	SINGLES kg		730	875	1030	1180	1320	1450	1600									
	DUALS kg		640	770	910	1040	1160	1280	1410									
	TRIPLES kg		600	720	840	970	1080	1190	1310									

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
320/85R34	LI						121		127		131	133					
	SINGLES kg		800	975	1120	1285	1450	1600	1750	1850	1950	2060					
	DUALS kg		700	860	990	1130	1280	1410	1540	1630	1720	1810					
	TRIPLES kg		660	800	920	1050	1190	1310	1440	1520	1600	1690					
320/85R38	LI						123		129		133	135	138	141	143		
	SINGLES kg		850	1030	1180	1360	1550	1700	1850	1950	2060	2180	2360	2575	2725		
	DUALS kg		750	910	1040	1200	1360	1500	1630	1720	1810	1920	2080	2270	2400		
	TRIPLES kg		700	840	970	1120	1270	1390	1520	1600	1690	1790	1940	2110	2230		
320/90R42	LI						126		133		136	139					
	SINGLES kg		950	1120	1320	1500	1700	1900	2060	2180	2240	2430					
	DUALS kg		840	990	1160	1320	1500	1670	1810	1920	1970	2140					
	TRIPLES kg		780	920	1080	1230	1390	1560	1690	1790	1840	1990					
320/90R46	LI						127		135		138	140	144	146	148		
	SINGLES kg		975	1180	1360	1550	1750	1950	2180	2300	2360	2500	2800	3000	3150		
	DUALS kg		860	1040	1200	1360	1540	1720	1920	2020	2080	2200	2460	2640	2770		
	TRIPLES kg		800	970	1120	1270	1440	1600	1790	1890	1940	2050	2300	2460	2580		
320/90R50	LI						129		136		140	142	145	148			
	SINGLES kg		1030	1250	1450	1650	1850	2060	2240	2360	2500	2650	2900	3150			
	DUALS kg		910	1100	1280	1450	1630	1810	1970	2080	2200	2330	2550	2770			
	TRIPLES kg		840	1030	1190	1350	1520	1690	1840	1940	2050	2170	2380	2580			
320/90R54	LI						131		138		141	143	146	149			
	SINGLES kg		1060	1285	1500	1700	1950	2120	2360	2500	2575	2725	3000	3250			
	DUALS kg		930	1130	1320	1500	1720	1870	2080	2200	2270	2400	2640	2860			
	TRIPLES kg		870	1050	1230	1390	1600	1740	1940	2050	2110	2230	2460	2670			
340/85R24	LI						119		125								
	SINGLES kg		750	900	1030	1180	1360	1500	1650								
	DUALS kg		660	790	910	1040	1200	1320	1450								
	TRIPLES kg		620	740	840	970	1120	1230	1350								
340/85R28	LI						121		127								
	SINGLES kg		800	950	1120	1285	1450	1600	1750								
	DUALS kg		700	840	990	1130	1280	1410	1540								
	TRIPLES kg		660	780	920	1050	1190	1310	1440								
360/70R20	LI						113		120		125	129					
	SINGLES kg		630	750	875	1000	1150	1250	1400	1500	1650	1850					
	DUALS kg		550	660	770	880	1010	1100	1230	1320	1450	1630					
	TRIPLES kg		520	620	720	820	940	1030	1150	1230	1350	1520					

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
360/70R28	LI						118		125								
	SINGLES kg		730	875	1030	1180	1320	1500	1650								
	DUALS kg		640	770	910	1040	1160	1320	1450								
	TRIPLES kg		600	720	850	970	1080	1230	1350								
380/70R24	LI						119		125								
	SINGLES kg		750	900	1030	1180	1360	1500	1650								
	DUALS kg		660	790	910	1040	1200	1320	1450								
	TRIPLES kg		620	740	840	970	1120	1230	1350								
380/70R28	LI						121		127								
	SINGLES kg		800	950	1120	1285	1450	1600	1750								
	DUALS kg		700	840	990	1130	1280	1410	1540								
	TRIPLES kg		660	780	920	1050	1190	1310	1440								
380/80R38	LI						130		137		140	142					
	SINGLES kg		1030	1250	1450	1650	1900	2060	2300	2430	2500	2650					
	DUALS kg		910	1100	1280	1450	1670	1810	2020	2140	2200	2330					
	TRIPLES kg		840	1030	1190	1350	1560	1690	1890	1990	2050	2170					
380/85R24	LI						124		131								
	SINGLES kg		875	1060	1250	1400	1600	1750	1950								
	DUALS kg		770	930	1100	1230	1410	1540	1720								
	TRIPLES kg		720	870	1030	1150	1310	1440	1600								
380/85R28	LI						126		133								
	SINGLES kg		950	1150	1320	1500	1700	1900	2060								
	DUALS kg		840	1010	1160	1320	1500	1670	1810								
	TRIPLES kg		780	940	1080	1230	1390	1560	1690								
380/85R30	LI						127		135								
	SINGLES kg		975	1180	1360	1550	1750	1950	2180								
	DUALS kg		860	1040	1200	1360	1540	1720	1920								
	TRIPLES kg		800	970	1120	1270	1440	1600	1790								
380/85R34	LI						129		137		140	142	145				
	SINGLES kg		1030	1250	1450	1650	1850	2060	2300	2430	2500	2650	2900				
	DUALS kg		910	1100	1280	1450	1630	1810	2020	2140	2200	2330	2550				
	TRIPLES kg		840	1030	1190	1350	1520	1690	1890	1990	2050	2170	2380				
385/85R34	LI						130		138		141	143	146				
	SINGLES kg		1060	1285	1500	1700	1900	2120	2360	2430	2575	2725	3000				
	DUALS kg		930	1130	1320	1500	1670	1870	2080	2140	2270	2400	2640				
	TRIPLES kg		870	1050	1230	1390	1560	1740	1940	1990	2110	2230	2460				
380/90R46	LI						137		144		147	149	152				
	SINGLES kg		1285	1500	1750	2000	2300	2500	2800	2900	3075	3250	3550				
	DUALS kg		1130	1320	1540	1760	2020	2200	2460	2550	2710	2860	3120				
	TRIPLES kg		1050	1230	1440	1640	1890	2050	2300	2380	2520	2670	2910				

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
380/90R50	LI						138		145		148	151					
	SINGLES kg		1320	1600	1850	2120	2360	2650	2900	3075	3150	3450					
	DUALS kg		1160	1410	1630	1870	2080	2330	2550	2710	2770	3040					
	TRIPLES kg		1080	1310	1520	1740	1940	2170	2380	2520	2580	2830					
380/90R54	LI						140		146		150	152					
	SINGLES kg		1360	1650	1950	2180	2500	2725	3000	3150	3350	3550					
	DUALS kg		1200	1450	1720	1920	2200	2400	2640	2770	2950	3120					
	TRIPLES kg		1120	1350	1600	1790	2050	2230	2460	2580	2750	2910					
380/105R50	LI						143		150		153	155	158	161	163	165	168
	SINGLES kg		1500	1800	2120	2430	2725	3000	3350	3450	3650	3875	4250	4625	4875	5150	5600
	DUALS kg		1320	1580	1870	2140	2400	2640	2950	3040	3210	3410	3740	4070	4290	4530	4930
	TRIPLES kg		1230	1480	1740	1990	2230	2460	2750	2830	2990	3180	3490	3790	4000	4220	4590
385/85R34	LI						129		137		140	142	145				
	SINGLES kg		1030	1250	1450	1650	1850	2060	2300	2430	2500	2650	2900				
	DUALS kg		910	1100	1280	1450	1630	1810	2020	2140	2200	2330	2550				
	TRIPLES kg		850	1030	1190	1350	1520	1690	1890	1990	2050	2170	2380				
420/70R24	LI						123		130								
	SINGLES kg		875	1030	1215	1400	1550	1750	1900								
	DUALS kg		770	910	1070	1230	1360	1540	1670								
	TRIPLES kg		720	840	1000	1150	1270	1440	1560								
420/80R46	LI						139		145		149	151	154	156	159	161	
	SINGLES kg		1320	1600	1850	2120	2430	2650	2900	3075	3250	3450	3750	4000	4375	4625	
	DUALS kg		1160	1410	1630	1870	2140	2330	2550	2710	2860	3040	3300	3520	3850	4070	
	TRIPLES kg		1080	1310	1520	1740	1990	2170	2380	2520	2670	2830	3080	3280	3590	3790	
420/85R24	LI						129		137								
	SINGLES kg		1030	1250	1450	1650	1850	2060	2300								
	DUALS kg		910	1100	1280	1450	1630	1810	2020								
	TRIPLES kg		840	1030	1190	1350	1520	1690	1890								
420/85R26	LI						131		138								
	SINGLES kg		1060	1285	1500	1700	1950	2120	2360								
	DUALS kg		930	1130	1320	1500	1720	1870	2080								
	TRIPLES kg		870	1050	1230	1390	1600	1740	1940								
420/85R28	LI						132		139								
	SINGLES kg		1120	1320	1550	1750	2000	2240	2430								
	DUALS kg		990	1160	1360	1540	1760	1970	2140								
	TRIPLES kg		920	1080	1270	1440	1640	1840	1990								
420/85R30	LI						133		140								
	SINGLES kg		1150	1360	1600	1850	2060	2300	2500								
	DUALS kg		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES kg		940	1120	1310	1520	1690	1890	2050								

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
420/85R34	LI						135		142		145	147					
	SINGLES kg		1215	1450	1700	1950	2180	2430	2650	2800	2900	3075					
	DUALS kg		1070	1280	1500	1720	1920	2140	2330	2460	2550	2710					
	TRIPLES kg		1000	1190	1390	1600	1790	1990	2170	2300	2380	2520					
420/85R38	LI						137		144								
	SINGLES kg		1285	1550	1800	2060	2300	2575	2800								
	DUALS kg		1130	1360	1580	1810	2020	2270	2460								
	TRIPLES kg		1050	1270	1480	1690	1890	2110	2300								
420/90R30	LI						135		142		145						
	SINGLES kg		1215	1450	1700	1900	2180	2430	2650	2800	2900						
	DUALS kg		1070	1280	1500	1670	1920	2140	2330	2460	2550						
	TRIPLES kg		1000	1190	1390	1560	1790	1990	2170	2300	2380						
460/85R30	LI						138		145								
	SINGLES kg		1320	1600	1850	2120	2360	2650	2900								
	DUALS kg		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES kg		1080	1310	1520	1740	1940	2170	2380								
460/85R34	LI						140	144	147								
	SINGLES kg		1400	1650	1950	2240	2500	2800	3075								
	DUALS kg		1230	1450	1720	1970	2200	2460	2710								
	TRIPLES kg		1150	1350	1600	1840	2050	2300	2520								
460/85R38	LI						142		149								
	SINGLES kg		1450	1750	2060	2360	2650	2900	3250								
	DUALS kg		1280	1540	1810	2080	2330	2550	2860								
	TRIPLES kg		1190	1440	1690	1940	2170	2380	2670								
460/85R42	LI						144		150								
	SINGLES kg		1550	1850	2180	2430	2800	3075	3350								
	DUALS kg		1360	1630	1920	2140	2460	2710	2950								
	TRIPLES kg		1270	1520	1790	1990	2300	2520	2750								
480/65R24	LI						127		133		137	140					
	SINGLES kg		975	1180	1360	1550	1750	1900	2060	2180	2300	2500					
	DUALS kg		860	1040	1200	1360	1540	1670	1810	1920	2020	2200					
	TRIPLES kg		800	970	1120	1270	1440	1560	1690	1790	1890	2050					
480/70R24	LI						131		138								
	SINGLES kg		1060	1285	1500	1700	1950	2120	2360								
	DUALS kg		930	1130	1320	1500	1720	1870	2080								
	TRIPLES kg		870	1050	1230	1390	1600	1740	1940								
480/70R28	LI						133		140								
	SINGLES kg		1150	1360	1600	1850	2060	2300	2500								
	DUALS kg		1010	1200	1410	1630	1810	2020	2200								
	TRIPLES kg		940	1120	1310	1520	1690	1890	2050								

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
480/70R30	LI						134		141		145	147	150	152			
	SINGLES kg		1180	1400	1650	1900	2120	2360	2575	2725	2900	3075	3350	3550			
	DUALS kg		1040	1230	1450	1670	1870	2080	2270	2400	2550	2710	2950	3120			
	TRIPLES kg		970	1150	1350	1560	1740	1940	2110	2230	2380	2520	2750	2910			
480/70R34	LI						136		143		146	149	152	155			
	SINGLES kg		1250	1500	1750	2000	2240	2500	2725	2900	3000	3250	3550	3875			
	DUALS kg		1100	1320	1540	1760	1970	2200	2400	2550	2640	2860	3120	3410			
	TRIPLES kg		1030	1230	1440	1640	1840	2050	2240	2380	2460	2670	2910	3180			
480/70R38	LI						138		145								
	SINGLES kg		1320	1600	1850	2120	2360	2650	2900								
	DUALS kg		1160	1410	1630	1870	2080	2330	2550								
	TRIPLES kg		1080	1310	1520	1740	1940	2170	2380								
480/80R30	LI						139		145								
	SINGLES kg		1320	1600	1850	2120	2430	2650	2900	3075	3250	3450	3750	4000	4375		
	DUALS kg		1160	1410	1630	1870	2140	2330	2550	2710	2860	3040	3300	3520	3850		
	TRIPLES kg		1080	1310	1520	1740	1990	2170	2380	2520	2670	2830	3080	3280	3590		
480/80R38	LI						142		149								
	SINGLES kg		1500	1800	2060	2360	2650	3000	3250								
	DUALS kg		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES kg		1230	1480	1690	1940	2170	2460	2670								
480/80R42	LI						144		151		154						
	SINGLES kg		1550	1850	2180	2500	2800	3150	3450	3650	3750						
	DUALS kg		1360	1630	1920	2200	2460	2770	3040	3210	3300						
	TRIPLES kg		1270	1520	1790	2050	2300	2580	2830	2990	3080						
480/80R46	LI						145		152		155	158					
	SINGLES kg		1650	1950	2300	2575	2900	3250	3550	3750	3875	4250					
	DUALS kg		1450	1720	2020	2270	2550	2860	3120	3300	3410	3740					
	TRIPLES kg		1350	1600	1890	2110	2380	2670	2910	3080	3180	3490					
480/80R50	LI						147		154		157	159					
	SINGLES kg		1700	2060	2360	2725	3075	3450	3750	3875	4125	4375					
	DUALS kg		1500	1810	2080	2400	2710	3040	3300	3410	3630	3850					
	TRIPLES kg		1390	1690	1940	2230	2520	2830	3080	3180	3380	3590					
480/85R34	LI						142		149								
	SINGLES kg		1500	1800	2060	2360	2650	3000	3250								
	DUALS kg		1320	1580	1810	2080	2330	2640	2860								
	TRIPLES kg		1230	1480	1690	1940	2170	2460	2670								
520/70R38	LI						143		150								
	SINGLES kg		1500	1800	2120	2360	2725	3000	3350								
	DUALS kg		1320	1580	1870	2080	2400	2640	2950								
	TRIPLES kg		1230	1480	1740	1940	2240	2460	2750								

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC UNITS OF MEASURE

TIRE SIZE		INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
			kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
			bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
520/85R34		LI						146		154		157	159	162				
	SINGLES kg		1700	2000	2360	2725	3000	3350	3750	3875	4125	4375	4750					
	DUALS kg		1500	1760	2080	2400	2640	2950	3300	3410	3630	3850	4180					
	TRIPLES kg		1390	1640	1940	2230	2460	2750	3080	3180	3380	3590	3900					
520/85R38		LI						148		155								
	SINGLES kg		1750	2120	2500	2800	3150	3550	3875									
	DUALS kg		1540	1870	2200	2460	2770	3120	3410									
	TRIPLES kg		1440	1740	2050	2300	2580	2910	3180									
520/85R42		LI						150		157		160	162	165				
	SINGLES kg		1850	2240	2575	3000	3350	3750	4125	4250	4500	4750	5150					
	DUALS kg		1630	1970	2270	2640	2950	3300	3630	3740	3960	4180	4530					
	TRIPLES kg		1520	1840	2110	2460	2750	3080	3380	3490	3690	3900	4220					
520/85R46		LI						151		158								
	SINGLES kg		1950	2300	2725	3075	3450	3875	4250									
	DUALS kg		1720	2020	2400	2710	3040	3410	3740									
	TRIPLES kg		1600	1890	2230	2520	2830	3180	3490									
540/65R24		LI						134		140								
	SINGLES kg		1180	1400	1650	1850	2120	2300	2500									
	DUALS kg		1040	1230	1450	1630	1870	2020	2200									
	TRIPLES kg		970	1150	1350	1520	1740	1890	2050									
540/65R30		LI						137		143		147	150					
	SINGLES kg		1285	1550	1800	2060	2300	2575	2725	2900	3075	3350						
	DUALS kg		1130	1360	1580	1810	2020	2270	2400	2550	2710	2950						
	TRIPLES kg		1050	1270	1480	1690	1890	2110	2230	2380	2520	2750						
540/65R34		LI						140		145		149	152					
	SINGLES kg		1360	1650	1900	2180	2500	2725	2900	3075	3250	3550						
	DUALS kg		1200	1450	1670	1920	2200	2400	2550	2710	2860	3120						
	TRIPLES kg		1120	1350	1560	1790	2050	2230	2380	2520	2670	2910						
540/65R38		LI						141		147								
	SINGLES kg		1450	1750	2000	2300	2575	2800	3075									
	DUALS kg		1280	1540	1760	2020	2270	2460	2710									
	TRIPLES kg		1190	1440	1640	1890	2110	2300	2520									
580/85R42		LI						156		163		166	168					
	SINGLES kg		2180	2650	3075	3550	4000	4375	4875	5000	5300	5600						
	DUALS kg		1920	2330	2710	3120	3520	3850	4290	4400	4660	4930						
	TRIPLES kg		1790	2170	2520	2910	3280	3590	4000	4100	4350	4590						
600/65R28		LI						142		148		152	154					
	SINGLES kg		1500	1750	2060	2360	2650	2900	3150	3350	3550	3750						
	DUALS kg		1320	1540	1810	2080	2330	2550	2770	2950	3120	3300						
	TRIPLES kg		1230	1440	1690	1940	2170	2380	2580	2750	2910	3080						

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
600/65R38	LI						147		153		156	159	162	165			
	SINGLES kg		1700	2060	2360	2725	3075	3350	3650	3875	4000	4375	4750	5150			
	DUALS kg		1500	1810	2080	2400	2710	2950	3210	3410	3520	3850	4180	4530			
	TRIPLES kg		1390	1690	1940	2230	2520	2750	2990	3180	3280	3590	3900	4220			
600/70R28	LI						145		152		155	157	161	164			
	SINGLES kg		1650	1950	2300	2575	2900	3250	3550	3750	3875	4125	4625	5000			
	DUALS kg		1450	1720	2020	2270	2550	2860	3120	3300	3410	3630	4070	4400			
	TRIPLES kg		1350	1600	1890	2110	2380	2670	2910	3080	3180	3380	3800	4100			
600/70R30	LI						146		153		156	158	162				
	SINGLES kg		1650	2000	2360	2650	3000	3350	3650	3875	4000	4250	4750				
	DUALS kg		1450	1760	2080	2330	2640	2950	3210	3410	3520	3740	4180				
	TRIPLES kg		1350	1640	1940	2170	2460	2750	2990	3180	3280	3490	3900				
620/70R42	LI						153		160		164	166					
	SINGLES kg		2060	2430	2900	3250	3650	4125	4500	4750	5000	5300					
	DUALS kg		1810	2140	2550	2860	3210	3630	3960	4180	4400	4660					
	TRIPLES kg		1690	1990	2380	2670	2990	3380	3690	3900	4100	4350					
650/65R38	LI						151		157		160	163	166				
	SINGLES kg		1900	2300	2650	3075	3450	3750	4125	4375	4500	4875	5300				
	DUALS kg		1670	2020	2330	2710	3040	3300	3630	3850	3960	4290	4660				
	TRIPLES kg		1560	1890	2170	2520	2830	3080	3380	3590	3690	4000	4350				
650/75R32	LI						154		161		164	166	169	172			
	SINGLES kg		2060	2500	2900	3350	3750	4125	4625	4875	5000	5300	5800	6300			
	DUALS kg		1810	2200	2550	2950	3300	3630	4070	4290	4400	4660	5100	5540			
	TRIPLES kg		1690	2050	2380	2750	3080	3380	3790	4000	4100	4350	4760	5170			
650/85R38	LI						160		167		170	173					
	SINGLES kg		2500	3000	3550	4000	4500	5000	5450	5800	6000	6500					
	DUALS kg		2200	2640	3120	3520	3960	4400	4800	5100	5280	5720					
	TRIPLES kg		2050	2460	2910	3280	3690	4100	4470	4760	4920	5330					
710/70R38	LI						159		166		169	171					
	SINGLES kg		2430	2900	3350	3875	4375	4875	5300	5600	5800	6150					
	DUALS kg		2140	2550	2950	3410	3850	4290	4660	4930	5100	5410					
	TRIPLES kg		1990	2380	2750	3180	3590	4000	4350	4590	4760	5040					
710/70R42	LI						160		168		171	173					
	SINGLES kg		2500	3000	3550	4000	4500	5000	5600	5800	6150	6500					
	DUALS kg		2200	2640	3120	3520	3960	4400	4930	5100	5410	5720					
	TRIPLES kg		2050	2460	2910	3280	3690	4100	4590	4760	5040	5330					

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com

METRIC UNITS OF MEASURE

TIRE SIZE	INFLATION	LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES															
		kPa	40	60	80	100	120	140	160	180	200	240	280	320	360	400	440
		bar	0.4	0.6	0.8	1	1.2	1.4	1.6	1.8	2	2.4	2.8	3.2	3.6	4	4.4
750/65R26	LI						153		159		163	166	169				
	SINGLES kg		2060	2430	2900	3250	3650	4000	4375	4625	4875	5300	5800				
	DUALS kg		1810	2140	2550	2860	3210	3520	3850	4070	4290	4660	5100				
	TRIPLES kg		1690	1990	2380	2670	2990	3280	3590	3790	4000	4350	4760				
800/65R32	LI						159		166		169	172					
	SINGLES kg		2430	3000	3450	4000	4375	4875	5300	5600	5800	6300					
	DUALS kg		2140	2640	3040	3520	3850	4290	4660	4930	5100	5540					
	TRIPLES kg		1990	2460	2830	3280	3590	4000	4350	4590	4760	5170					
800/70R38	LI						166		173		176	178	181				
	SINGLES kg		2900	3450	4125	4625	5300	5800	6500	6700	7100	7500	8250				
	DUALS kg		2550	3040	3630	4070	4660	5100	5720	5900	6250	6600	7260				
	TRIPLES kg		2380	2830	3380	3790	4350	4760	5330	5490	5820	6150	6770				
900/50R42	LI						161		168								
	SINGLES kg		2575	3075	3550	4125	4625	5150	5600								
	DUALS kg		2270	2710	3120	3630	4070	4530	4930								
	TRIPLES kg		2110	2520	2910	3380	3790	4220	4590								
900/60R32	LI						163		169		173	176					
	SINGLES kg		2650	3250	3750	4250	4875	5300	5800	6300	6500	7100					
	DUALS kg		2330	2860	3300	3740	4290	4660	5100	5540	5720	6250					
	TRIPLES kg		2170	2670	3080	3490	4000	4350	4760	5170	5330	5820					
900/75R32	LI						172		179		182	184					
	SINGLES kg		3550	4250	4875	5600	6300	7100	7750	8000	8500	9000					
	DUALS kg		3120	3740	4290	4930	5540	6250	6820	7040	7480	7920					
	TRIPLES kg		2910	3490	4000	4590	5170	5820	6360	6560	6970	7380					

NOTES:

1. For shipping purposes, tire inflation pressures may be increased to 30 psi (210 kPa). Inflation pressure must be adjusted to correct operating inflation before placing tires in service.
2. For transport service above 20 mph (30 km/h), recommended minimum inflation pressure is 8 psi (60 kPa).
3. For tires used in cyclic loading service see Table F1.
4. For transport service and operations which do not require sustained high torque, the following limits at various speeds apply with no change in inflation pressure.

MAX. SPEED	% CHANGE IN TABLE
10 mph (15 km/h)	+34% (except hillside combines)
15 mph (25 km/h)	+11% (except hillside combines)
20 mph (30 km/h)	+7%
25 mph (40 km/h)	None
30 mph (50 km/h)	None

Firestone

F A R M T I R E S

THE LEADER IN THE FIELD

FirestoneAg.com